



MIRA ADVANCE ATL FLEX 9.0kW

Operating Features

- Safe, precise & thermostatically controlled
- Adjustable temperature control
- Large, colour contrasting, rotary lever & buttons
- 2m hose
- LED backlit flow on/off buttons
- Endorsed by the RNIB & BEAB
- Colour contrasting panel to aid navigation
- Delayed shutdown for safer showering & reducing limescale

Thermostatic temperature control	
9.0 kW power rating	
Inlet connections – 15mm compression	
Outlet connection – ½" BSP male	
Supply - Mains pressure cold water	
Minimum dynamic pressure 0.5 bar	
Minimum static pressure 0.2 bar	
Maximum static pressure 10 Bar	
Surface mounted	
2 year guarantee	
*Recommended dynamic pressure of 1.0 bar for full flow performance	
Reference	06ES01



MIRA ADVANCE ATL FLEX EXTRA 9.0kW

Operating Features

- Link directly with a Primo XTRA shower . waste pump or Whale Instant Match™, eliminating the need for a flowswitch*
- Safe, precise & thermostatically controlled
- Adjustable temperature control
- Large, colour contrasting, rotary lever & buttons
- 2m hose
- LED backlit flow on/off buttons
- Endorsed by the RNIB & BEAB
- Colour contrasting panel to aid navigation
- Delayed shutdown for safer showering & reducing limescale

*Supplied separately.

Thermostatic temperature control	
9.0 kW power rating	
Inlet connections – 15mm compression	
Outlet connection – ½" BSP male	
Supply - Mains pressure cold water	
Minimum dynamic pressure 0.5 bar	
Minimum static pressure 0.2 bar	
Maximum static pressure 10 Bar	
Surface mounted	
2 year guarantee	
*Recommended dynamic pressure of 1.0 bar for full flow performance	
Reference	06ES03



MIRA SELECT FLEX

Operating Features

- Thermostatic control plus TMV2 & TMV3 approval for safe showering
- Separate flow & temperature controls with extended lever controls
- Maximum temperature stop
- Cool Touch technology reduces the surface temperature when in use
- 2m hose and 1m easy glide riser rail
- Can be corner mounted
- Variable pipe inlet centres for easy installation

Thermostatic temperature control	
Inlet connections – 15mm compression	
Outlet connection – ½" BSP flat face	
Maximum static pressure 10 bar	
Maximum maintained pressure 5 bar	
Factory preset temperature at 41°C	
Thermostatic shutdown with 2 seconds	
5 year guarantee	
*Minimum maintained pressure (gravity system) 0.1 bar	
Reference	06MS10



Plumbing system compatibility:

- Fully modulating combi boilers & instantaneous gas water heaters
- Gravity-fed hot & cold water supply
- Gravity-fed hot & cold pumped water supply
- Mains pressure hot & cold - unvented
- Mains pressure thermal store


TRITON SAFEGUARD T100 CARE 8.5kW
Operating Features

- Endorsed by the RNIB
- Unique three stage thermostatic performance
- Adjustable timed shutdown
- Adjustable maximum temperature stop
- Provision for a connection to a level access waste pump
- Phased shutdown
- Large push button Start/Stop
- Low pressure indicator
- Extended riser rail
- 2m hose
- Ergonomic rub clean showerhead with 5 spray patterns

Thermostatic temperature control	
8.5 kW power rating	
Inlet connections – 15mm compression	
Outlet connection – ½" BSP	
Mains cold water plumbing systems only	
Minimum running pressure 0.5 Bar @ 8l/min*	
Maximum static pressure 10 Bar	
Surface mounted	
2 year guarantee	
*Recommended minimum running pressure/flow for full performance 1 Bar @ 8l/min	
Reference	06ES20


TRITON SAFEGUARD PUMPED CARE 8.5kW
Operating Features

- Pumped for low water pressures
- Endorsed by the RNIB
- Unique three stage thermostatic performance
- Adjustable timed shutdown
- Adjustable maximum temperature stop
- Provision for a connection to a level access waste pump
- Phased shutdown
- Large push button Start/Stop
- Low pressure indicator
- Extended riser rail
- 2m hose
- Ergonomic rub clean showerhead with 5 spray patterns

Thermostatic pumped temperature control	
8.5 kW power rating	
Inlet connections – 15mm compression	
Outlet connection – ½" BSP	
Mains cold water plumbing systems only	
Minimum head pressure – 75mm	
Maximum head pressure – 10m	
Surface mounted	
2 year guarantee	
*Recommended minimum running pressure/flow for full performance 1 Bar @ 8l/min	
Reference	06ES21


Showers

- Electric or thermostatic TMV 3 approved
- Endorsed by RNIB & BEAB
- Link directly to waste pump options