

CONTOUR Mixer Shower

The only thermostatic & pressure balancing mixer shower available

Contour Mixer Shower

The versatile Contour Mixer Shower features precise thermostatic control, which recognizes and compensates for changes in water temperature to give you an extremely safe and satisfying shower. NHS, DO8 & TMV3 approved, Contour mixer shower reacts to the supply water temperature and adjusts the mixing proportions between hot and cold water. If the cold water pressure fails, the thermostat will react and close the water flow entirely, within 0.2 seconds, to prevent the risk of scalding.

Anti-tamper temperature control set at 38°F, which can be manually overridden, surface mountable and attractive, this type of mixer shower has wing shaped controls to assist those with restricted hand use. A water saving shower head supplies a maximum of 9 litres per minute, and has a 1.5metre riser rail kit for assisted bathing.

Contour Mixer shower is a WRAS approved product meeting all water bylaws, and can also achieve water and energy savings of up to 70%, without compromising performance.

Supplied with a 5 year guarantee on temperature and pressure stability and against anti calcification.

Options available include a 1.5 bar pump for areas restrained by low water pressure and an Anti-Legionella kit for low use situations.

When exposed pipework is present or preferred a surface mounted version of Contour Mixer Shower is available on request.



Exposed kit

! CONTOUR MIXER SHOWER IS INTENDED FOR USE ON HIGH PRESSURE WATER SYSTEMS OF 1.0 BAR AND ABOVE

Anti-Legionella Kit

Using our safe thermostatic and pressure balanced mixer valve as above, but including an Anti-Legionella hose kit.

Standard shower heads and hoses normally retain significant amounts of water, which if left for a period of time provides ideal growth conditions for the rapid development of the deadly legionella bacteria.

Using a combination of a specially designed hose, with no dead leg loop, and a dump valve, the riser kit and mixer completely dispels all water as the shower is switched off.

Reference

Contour Mixer Shower – Anti-legionella	06MS02
Contour Mixer Shower – Anti-legionella & Pump	06MS04



Reference

Contour Mixer Shower	06MS01
Contour Mixer Shower Exposed Kit	06MS01E
Contour Mixer Shower & Pump	06MS03





Mira Advance ATL Shower Heater

Electric showers are connected to the mains cold water with an exclusive, permanent electrical supply. They heat water as it is used, and as such are the most economical showers to run.

The Mira Advance ATL is designed specifically for the less able, and provides precise temperature control for safe showering.

- Approved by BEAB to meet new standards of safety for electrical goods for use by the elderly, young or infirm
- Specifically designed for the less able and featuring thermostatic control for consistent water temperature
- Separate temperature and flow controls allow you to leave the temperature at a preferred setting
- Temperature settings range from 37° to 48° and protect the user from selecting unsafe temperatures.
- 2 metre hose and 1 metre riser rail where assisted bathing is required
- Independent stop button and flow controls, situated in ascending order for ease of selection
- Power rating 8.7kw

Reference

Mira Advance ATL Shower Heater	06ES01
--------------------------------	--------

AQUIV8 WATER SAVING SHOWER HEAD



Normal water droplet



Aquiv8 water droplet

Normal showers flow at a rate between 15-30 litres per minute, whilst the rate required for an adequate shower is only between 6-8 litres. It is evident that a significant amount of water is wasted in a normal shower and the potential for substantial savings is high.

The Aquiv8's intelligent design mixes air within the water droplet, reducing the water content by as much as 70%, without diminishing the wetting effect.

The water droplet remains intact, providing a power shower feeling without wasting excess water or sacrificing performance.

- Achieve water and energy savings by up to 70%, without compromising performance
- Anti scale
- Flow rate 8 litres per minute
- Maximum pressure 12.0 bar, minimum 1.0 bar
- 3 year guarantee
- Retro-fit to an existing mixer shower unit, 1/2" BSP connection

Reference

Aquiv8 Shower Head	06MSH01
--------------------	---------

Mixer & Electric showers

- Contour Mixer shower
- Contour Anti-Legionella Mixer shower
- Mira Advance shower heater