

CONTOUR Tilesafe



Water penetration through ceramic tiles in bath / shower rooms and wet floor areas caused by leaks, floods, substrate movement and grout failure can lead to extensive costs and inconvenience to those involved.

Contour Tilesafe, is a new concept developed to provide waterproofing beneath ceramic tiles in shower and wet floor areas and can be applied in a matter of hours, ready for immediate tiling.

Tilesafe is a heavy duty, flexible, self adhesive membrane, consisting of a thick rubber modified bitumen waterproof layer incorporating a woven glass fibre mesh on one face.

Tilesafe kit comprises all components necessary to provide the ideal waterproofing solution. Includes, primer, reinforcing tape, membrane, jointing compound and putty.




1 Prime all surfaces with Tilesafe primer and allow to dry (20mins)



2 Apply Tilesafe reinforcing tape to all wall to wall as well as wall to floor junctions. Reinforcement tape is also required at all Tilesafe membrane butt joints.




3 Apply the self adhesive Tilesafe membrane to walls and floor. Joints are simply butted with 1-2mm gap over previously applied reinforcement tape



4 Apply Tilesafe jointing compound into all butt joints



5 Remove the special Tilesafe membrane release film and begin tiling.



6 Tilesafe membrane is simple to detail around service entries and seal with either the supplied jointing compound or putty.

- No curing time, ideal for 'fast track' installation. Can be installed in hours, allowing for immediate tiling
- Forms a strong permanent bond
- Will accommodate differential movement between building elements, which is the principle weakness in alternative systems
- Simple to detail in critical areas
- Cost effective solution
- Compatible with all quality, conventional tile adhesives
- Available as 5m square kit or 10m square kit
- Provides long term waterproofing, to prevent water damage to any rooms below bathrooms, shower and wet floor areas. Also suitable for use in domestic situations
- Can be cold applied directly to masonry, concrete, screed, plasterboard and plywood.

	REFERENCE
5m Kit	15TS5
10m Kit	15TS10

Technical Helpline:
0845 402 9924

Tilesafe

- **Heavy duty, self adhesive, waterproof membrane**
- **Provides long term waterproofing**
- **No curing time for fast track installation**