

# THE ROSTHERNE BATH

## IMPORTANT INSTRUCTIONS FOR CUSTOMER

**PLEASE READ CAREFULLY AND RETAIN FOR FURTHER USE.**  
**IMPROPER USE OR CARE CAN INVALIDATE THE WARRANTY.**

### OPERATING INSTRUCTIONS

The Rosthenre Bath features a watertight door which is held in a locked position by means of two latch locks on the LHS and RHS of doorway sides. The locks are released by means of the Lock Lever on face of door.

Always leave door in an open folded down position when bath is not in use. This is to prevent over compression & wearing out of the door rubber seal.

1. Approach bath and sit on doorway ledge on far left hand side or right hand side as is preferable. Lift legs over into bath and push back towards bath end side.
2. Firmly hold Door Grip on the inner face of door and pull over to slum shut door ensuring locks are engaged on both sides. If lock furthest away has not engaged pull on Door Grip again whilst still in this position.
3. The bath is now watertight and ready for use.
4. After bathing, remain in bath until all the water is drained on release of the bath waste.
5. Turn door Lock Lever on front face of door (in either direction) to release locks whilst holding Door Grip on inner face. Carefully lower door down to a fully open position before letting go of Grip.
6. Exit the bath and leave the door folded down in an open position.

- NEVER ATTEMPT TO OPEN DOOR WHEN BATH IS FILLED WITH WATER
- DO NOT LEAN ON DOOR OR USE FOR SUPPORT EXCESSIVELY

## CARE AND MAINTENANCE

The Rostherne Bath is manufactured to a very high standard in G.R.P. (Reinforced Plastic) to ensure its durability and appearance is maintained over many years of use. It has a robust, smooth and warm surface, which is non-porous, resistant to dirt and bacteria and easy to clean and maintain.

The Rostherne bath will give many years of service and continue to look good if cleaned correctly and treated with care.

## CLEANING

1. As with standard baths, cleaning will vary subject to the scale residue dependant on the hard or soft water level. In soft water areas, wash down with warm water and detergent applied with a soft cloth or sponge. In hard water areas, non-abrasive or mild acid cleansers can be used. Clean regularly followed by wiping with a dry soft cloth.

Widely available proprietary plastic/enamel bath cleansers are ideal cleaning agents which offer the advantage of a polished shine without rubbing down.

For the extra sparkle, and to further preserve the surface, the Bath can be gently polished occasionally. Beeswax and Brasso (Brass Polish) are suitable for this purpose.

2. Lubricate and polish door latch locks at least once a year (subject to the chlorine content in the water). A standard lubricant such as “WD 40” or “3 in 1 oil” would be adequate.
3. The white silicone seal along bath door sides must be cleaned occasionally to ensure no build up of foreign deposits. Use detergent and warm water applied with a sponge or soft cloth. Apply gently and refrain from excessive rubbing.
4. All chrome or gold plated furniture should be wiped down dry after use. Clean with soapy water and buff with a dry soft cloth. Note: Surfaces can easily be damaged by acid, abrasive detergent or rough sponge.

## CAUTION

- **LEAVE DOOR IN OPEN/FOLDED DOWN POSITION WHEN BATH IS NOT IN USE TO PRESERVE THE SEAL.**
- **KEEP THE WHITE SILICONE SEAL FREE OF ANY BUILD UP OF DEPOSITS. CLEAN GENTLY AND AVOID UNNECESSARY HANDLING.**
- **DO NOT APPLY ANY UNDUE FORCE TO THE BATH DOOR. ALWAYS HANDLE AND SUPPORT DOOR WHEN OPENING.**



SNB Ltd 37 Warren Street London W1T 6AD  
13  
EN 14516: CLASS 2