



**MIRA ADVANCE
ATL FLEX 8.7kW
& FLEX EXTRA 8.7kW**



**MIRA ADVANCE ATL FLEX
LOW PRESSURE 9.0kW**



TRITON OMNICARE 8.5kW



ELECTRIC SHOWERS

MIRA ADVANCE ATL FLEX 8.7kW

- Thermostatic control & Opti-flo Pro™ technology for consistent showering.
- Easily accessible, light touch controls & high contrast on critical touch points.
- Large easy press buttons with audible features for the visually impaired:
 - Audible beeps when turning on / off & when desired temperature reached.
 - Audible clicks when turning temperature dial.
- 2m hose, 1m riser rail with friction grip shower head holder.
- Anti-glare matte finish panel.
- Mira Clearscale Pro technology reduces limescale build up.
- Simple to commission for easy installation.

Advance ATL Flex Extra 8.7kW:

- Integral wired connection links directly to a Contour P12 shower waste pump or bluetooth connection to pair with a Whale Instant Match pump.

Mira Advance Flex Fittings Kit

- 2m hose, 1m riser rail with friction grip shower head holder.
- Compatible with any shower on any system & can be wall or corner mounted.

MIRA ADVANCE ATL FLEX LOW PRESSURE 9.0kW

- With an integrated pump for low pressure areas.
- Provides a consistent flow at low pressure (min 80mm head pressure).
- Compatible with cold water systems only.
- Min pressure 0.008 bar (80mm), Maxi pressure 1.0 bar (10m head).
- Maximum static pressure 1.0 bar (10m head).

TRITON OMNICARE 8.5kW

- Constantly regulating temperature within +/-1°C, for max temp assurance.
- Soft press Start / Stop button requires very little force.
- Centralised, low resistance, looped lever handle for intuitive use.
- 2m anti twist shower hose.
- Multiple cable & water entry points.
- Connects to both analogue & digital shower waste pumps.
- Link directly to a **P12 shower waste pump** by a hardwire connection.
- Extended riser rail kit / dual purpose grab riser rail kit available with a support load maximum of 150kg.
- Designed with retro-fitting in mind.

MIRA ADVANCE ATL SPECIFICATION

Temperature control	Thermostatic +/-1°C with Opti-flo Pro™
Power ratings	8.7kW 240V AC (8.0kW 230V AC)
Supply ratings	40 amp (8.7kW)
Adjustable Max temp	4 max temp settings (41°C - 48°C)
Phased shutdown	Yes
Start / Stop	Large easy press power button High contrast on critical touch points
Audible feedback	Yes to assist the visually impaired
Built in fault diagnosis	Yes
Inlet connections	15mm compression or ½" BSP male
Outlet connections	½" BSP male
Min maintained pressure	0.5 bar (5m head), (1.0 bar BEAB Care)
Min maintained pressure	5.0 bar @ (50 metre head)
Maximum static pressure	10.0 bar (100 metre head)

TRITON OMNICARE SPECIFICATION

Temperature stability	Thermostatic +/-1°C with Tri-Therm™
Power ratings	8.5kW & 9.5kW (@ 240V)
Adjustable Max temp	41°C, 43°C or 47°C with Safe-Set™
Timed auto shutdown	5, 10, 20, or 30 mins (20 mins default)
Start / Stop	Soft press button Start / Stop button & temperature control dial
Audible feedback	Start / Stop & timer end confirmation
Visual indicators	Power on / timer / low flow illumination
Water connection	15mm swivel inlet (up / down)
Terminal block	16mm max cable
Waste pump connection	Analogue & Digital (hardwired)
Water supply	Mains cold water
Water pressure min	1bar @ 8 litres / min
Water pressure max	10 bar (static)

Description	Reference
Advance ATL Flex 8.7kW	06ES06
Advance ATL Flex Extra 8.7kW	06ES07
Advance Flex Fittings Kit	06ES-MAFK
Advance ATL Flex Low Pressure 9.0kW	06ES01-LP
Omnicare 8.5kW	06ES60
Omnicare 9.5kW	06ES61
Omnicare Grab 8.5kW	06ES60GB
Omnicare Grab 9.5kW	06ES61GB
Omnicare 3 Year Extended Guarantee	06ES63-3Y
Omnicare 5 Year Extended Guarantee	06ES65-5Y



REDRING SELECTRONIC PREMIER CARE 8.5, 9.5 & 10.8kW



BRISTAN JOY CARE 8.5kW



REDRING SELECTRONIC SPECIFICATION

Thermostatic control	Control accuracy +/-0.5°C
Start up temperature	40, 41 or 43°C
Temperature range	25 - 46°C
Running pressure psi (bar)	10 (0.7) - 140 (10)
Electrical connection	Right hand side only
Phased shutdown	Yes
Start / Stop	Large easy press power button
Pipe connection	Top, bottom & rear (right hand side)
Water connection	½" BSP compression fitting
Cable size recommended	8.5kW: 6 - 10mm ² 40 Amps 9.5kW: 6 - 10mm ² 40 Amps 10.8kW: 10 - 16mm ² 45 Amps

REDRING SELECTRONIC PREMIER CARE

- Accurate, temperature control to within +0.5° for comfortable & safe showering.
- Matt anti-glare finish within grey stripes & raised tactile easy push button controls with audible & visual indicators assist the visually impaired.
- Large LED digital temperature display.
- Phased shutdown safety protection for next user cool start up & scale protection.
- 3 maximum temperature limiter lock options 40°C, 41°C, 43°C, set at installation.
- Contoured surfaces & edges for safety.
- 30 minute auto switch off/on temp lock mode.
- Right hand side multi-entry connection options.
- 5-spray mode shower head with easy rub clean nozzles.
- 250kg* load bearing grab riser rail with reinforced 4 point fixing brackets.
- 2mtr anti-kink flexible shower hose for seated & carer assisted showering.
- WPC models supplied with RF receiver module for wireless pump connectivity, also has hard-wired pump connection options.
- 5 year UK warranty. **Requires registration with Redring within 30 days.**

(*subject to correct wall material fixing use).

BRISTAN JOY CARE SPECIFICATION

Inlet connection	15mm push swivel fit
Outlet connection	½" BSP male threaded
Minimum working pressure	0.5 Bar
Maximum working pressure	10.0 Bar
Static pressure range	0.2 - 10.0 Bar
System requirements	Mains cold water pressure only
Thermostatic	Yes
Maximum temperature setting	Yes
Auto shut off	Yes
3 power settings	Cold, warm & Eco & hot
Push Button On/Off	Yes, soft touch
Cable entry points	5
Water entry points	5

BRISTAN JOY CARE 8.5kW

- Instantaneous 8.5kW electric shower drawing water direct from the mains supply, ideal for installations without stored hot water & second bathrooms.
- Factory settings can be adjusted at installation to suit the user requirements.
- Soft touch button, LED readout, audible bleeps (can be deactivated), lever dial & contrasting finish.
- Flexible fit with multiple water & cable entry points, digital fault code display & simple commissioning means a fast, fuss-free, new or replacement installation.
- Phased shut down feature ensures all hot water is flushed out of the shower after use prolonging the shower life.
- Adjustable 1 metre riser rail comes complete with adjustable top / bottom brackets, ideal to cover existing riser holes & tile joints.
- ThermoSafe™ Technology: Regulates the output water to minimise high/dangerous output temperatures for a safer showering experience.

Description	Reference
Selectronic Premier Care 8.5kW	06ES44-85
Selectronic Premier Care 9.5kW	06ES45-95
Selectronic Premier Care 10.8kW	06ES46-108
Selectronic Premier Care Pumped 8.5kW	06ES47-85
Selectronic Premier Care Pumped 9.5kW	06ES48-95
Joy Care 8.5kW	06ES50-85

Full technical details for electric showers can be found at www.contour-showers.co.uk

